

TESLA TA36FFUL-1232IAW



FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Top plate/cover improved, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only), WIFI, I FEEL

Capacity			12000BTU
Rated volt and frequency		V/Hz	220-240V~/50HZ
Mode			Cooling Heating
Rated capacity		W	3500(800-3800) 3600(800-4100)
Power input		W	1190(100-1500) 1150(100-1400)
Current input		A	5.5(0.6-6.7) 5.4(0.6-6.4)
SEER-SCOP/ Energy Class		W/W	6,21/A++ 4,04/A+
Operating range		(°C)	16~49°C -15~30°C
Energy consumption (per year, based on standard test results)		kwh	198 902
Dehumidifying		Kg/h	0.8
Degree of protection (IN) / (OUT)		(IP)	IPX0/IPX4
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I
Max. input consumption		W	1900
Max. current		A	9.5
Compressor		Model	GSD088RKNA6JV6B
		Type	DC
		Brand	Highly
Indoor	Fan motor	Model	YYK18-4B
		Power input	W
		Capacity	uF
		Indoor Fan Speed RPM	r/min
	Indoor fan	Dia. / Length	mm
	Indoor Air Circulation		m³/h
	Indoor Noise Level dB		dB(A)
	Net Dimension (LxWxH)		mm
	Packing Dimension (LxWxH)		mm
	Net Weight/Gross Weight		Kg
Outdoor	Fan motor	Model	D-24-8
		Power input	W
		Capacity	uF
		Outdoor Fan Speed RPM	r/min
	Outdoor fan	Length	mm
	Outdoor Noise Level dB		dB(A)
	Net Dimension (LxWxH)		mm
	Packing Dimension (LxWxH)		mm
	Net Weight/Gross Weight		Kg
	Refrigerant type/weight		g
Max. Discharge/Max. Suction pressure		Mpa	
Refrigerant piping	Liquid side / Gas side		mm
	Max. refrigerant pipe length / Max. difference in level		m